



DECLARATION OF PERFORMANCE

Nº: 14-591



1. Unique identification code of the product-type/batch number or other identification element

Impermax Polyurea H
Two component waterproofing product
Batch number on each label

Components	Trade name
Primers	Rayston Epoxy 100 / Humidity Primer
Waterproofing membrane	Impermax Polyurea H
Finish	Impertrans

2. Intended use

Liquid roof waterproofing

3. Manufacturer

Krypton Chemical
C/Martí i Franquès, 12
43890, L'Hospitalet de l'Infant (Tarragona, Spain)

4. Systems of assessment of verification of constancy of performance

3

5. Harmonized standard

Non applicable

6. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued

Approval body IETCC issued an ETA-06/0263 based on ETAG 005-6:2000. Nº1219

7. Notified body

Instituto de Ciencias de la Construcción Eduardo Torroja (IETCC)

8. Declared performance

Essential characteristics	Performance
External fire behaviour	B _{roof}
Fire class	F
Use life	W2
Climatic zone	S (Severe)
Use load	P4
Roof slope	S1 to S4
Minimum surface temperature	TL3
Maximum surface temperature	TH4
Hazardous components	Not declared

The performance of the product identified in points 1 and 2 is in conformity with the performance declared in point 8. This Declaration of Performance (DoP) is issued according of Regulation (EU) 305/2011 and under the sole responsibility of the manufacturer identified in point 3.

Signed by Raul Fernandez, Technical Manager on behalf of the manufacturer.
L'Hospitalet de l'Infant, November 14th 2014

